










# Pelican Search Lights & Remote Area Lighting Systems

Note: BLI = Battery level indicator

Product #	Product Image (not to scale)	Model No	Light Source	Lumens		Runtime		Beam Distance (metres)		Beam Spread in Degrees	12v Sockets	Modes	Battery Type	Battery Charging Time	Length Closed (cm)	Width Closed (cm)	Height Closed (cm)	Mast Height (cm)	Weight (kg)	Body Material	IECEX	Ingress Rating	Additional Information / Features	Colours Available
				High	Low	High	Low	High	Low															
40457		9410	LED	1203	553	4h	10h	430	287	-	-	On/Off, High, Low, Flashing	Lithium ion with BLI	7-8h	22.2	9.5	10.2	n/a	1.270	ABS	-	IPX4	Features: pivoting head, standing position. Includes: shoulder strap, AC charger and base.	Black, Yellow
40458		9415i	LED	392	144	4h	11h	392	234	-	-	On/Off, High, Low, Flashing	4 C NiMH with BLI	5.5h	22.2	9.5	10.2	n/a	1.650	Anti-static Impact Modified PC/PBT	IECEX	IPX4	Features: pivoting head, standing position. Includes: shoulder strap, AC charger and base.	Yellow
40459		9420XL	Cree LED	1000	500	2h	4h	-	-	58	1 Primary	On/Off, High, Low	Lithium ion with BLI	2h	73.7	-	-	157.5	3.810	Polycarbonate Resin	-	IP54	Includes: blow-moulded case, 2 x batteries, AC & DC charger, charging station & shoulder strap.	Black
40460		9430	High Flux LED	3000	1500	8h	15h	-	-	125	1 Primary, 1 Auxiliary	On/Off, High, Low, Flashing	12v Rechargeable Sealed with BLI	5h	40	20	23	82	10.270	-	-	IP54	Features: 360 degree rotating head. Includes: AC charger. Optional: Carry Backpack	Black, Yellow
40461		9455	High Flux LED	1600	800	5h	10h	-	-	125	-	On/Off, High, Low, Flashing	NiMH with BLI	8h	40	20	23	80	7.300	-	IECEX	IP54	Features: 360 degree rotating head. Includes: AC charger. Optional: Carry backpack	Yellow
40462		9440	High Flux LED	5300	1400	1.5h	8h	-	-	125	1 Primary	On/Off, High, Med, Low	Lithium ion with BLI	3h 45m	95	20	-	215.9	7.300	-	-	IP65	Features: pivoting head, quick deployment. Includes: shoulder strap and AC charger.	Black, Yellow
40463		9460	High Flux LED	12000	-	3h	24h	-	-	120	2 Primary	On/Off, User Adjustable Output, Flashing	12v Rechargeable Sealed with BLI	8h	59.1	35.6	23.5	201.9	27.700	-	-	IP54	Features: pivoting head, housed in Pelican tough case. Includes: AC charger.	Black, Yellow
40464		9470	High Flux LED	24000	-	2.75h	24h	-	-	120	4 Primary	On/Off, User Adjustable Output	12v Rechargeable Sealed with BLI	8h	63	50.8	29.8	208.3	47.600	-	-	IP54	Features: pivoting head, housed in Pelican tough case. Includes: AC charger.	Black, Yellow
40465		9490	High Flux LED	6000	-	3.5h	24h	-	-	125	1 Primary	On/Off, High, Med, Low, User Adjustable Output	12v Rechargeable Sealed with BLI	8h	50.8	16.5	28.6	182.9	14.510	-	-	IP54	Features: pivoting head, standing position. Includes: shoulder strap, AC charger.	Black, Yellow